

Fax Request

Description of special types – First mate last break contacts – selective loading

Connectors acc,DIN 41612 Types B.C.Q.R.F.H

Company																Phone															
First Name								Last Name								Fax															
Address																															
Address																Signature															

Based on W.E.connector described in catalog

Weitronic-Part-No.

Required Quantity

1/3

1/2

Type B,C,Q,R-Female Connectors

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
a																																
b																																
c																																

Type B,C,Q,R-Male Connectors

Mating Side

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
a																																
b																																
c																																

Backside

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
a																																
b																																
c																																

Type F

- ☐ Male Connectors
☐ Female Connectors

	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32
d																
b																
z																

Type H

- ☐ Male Connectors
☐ Female Connectors

	6	10	14	18	22	26	30
d							
z							

o : standard

△ : not assembled

+ : 0.8 mm premateing

x : 1.0 mm premateing

* : 1.5 mm premateing

- : 0.8 mm late mate

/ : 1.0 mm late mate